

Staplex®

High Volume Air Sampler



Model	TFIA	TFIA-F	TFIA-CDT	TFIA-FCDT
Contents				
Flow Meter	◎	◎	◎	◎
Flow Adjuster		◎		◎
Count Down Timer			◎	◎
Flow Range	0 ~ 2 m ³ /min. (0~2,000 Litter/min.)			
Power	メーカー標準電源電圧 AC110~125 V (ステップアップトランス別途要) AC100V 電源も使用可能 (但し最大流量不担保)			
Dimensions, cm	21.6	19.1	19.1	
Weight, kg	about 4.5			
Construction	堅牢で軽量のジュラルミン製			
Filters	TFA41 : 4 inch dia. (100 sheet/Box)			
	TFAGF41 : Glass Fiber Filter 4 inch dia. (100 sheet/Box)			
	TFAQ41 : Quartz Filter 4 inch dia. (100 sheet/Box)			
	and other			
Filter Holders	SH4 : for 4 inch dia. Filter Holder Assembly			
	and other			

ProTech Inc.

株式会社プロテック
埼玉県三郷市高州 4-65-1-404
Tel. 048-948-2177 Fax. 048-948-2178
kty-m-protech@work.odn.ne.jp
<https://www.kagaku.com/protech/>